

8AU1H-DEKA

SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	37Ah
Capacity at C/20	32Ah
Weight	23 lbs. (10 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) - 140°F (60°C)

For Charging Parameters please refer to www.mkbattery.com

Click on Technical Data, then on Photovoltaic Charging Parameters in the PV/Solar section

Vent	Self-sealing
Terminal	Y (T873)




Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

Valve-Regulated, Absorbed Glass Mat Technology




DIMENSIONS

Inches (mm)

Length	8.41 (214 mm)
Width	5.18 (132 mm)
Height	7.22 (183 mm) <i>Including terminal</i>

AGM Cycle Life vs Depth of Discharge at 25°C (77°F)
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

